



DSM 220

# | DSM |

## FLOOR SPACE OPTIMIZER



DSM 146

## FEATURES

- Capacity / Volume: 8% more than 2 units GSM 200
- 27 % less floor space than 2 units GSM 200
- 28% energy saving compared with 2 units GSM 200
- Patented Design

	DSM 146	DSM 220
Climate class	3LN1	3LN1
Ambient temperature range	+10 to +25	+10 to +25
Climate class 4 and 7 (4+)	n/a	n/a
Gross volume, litres	425	1697
Net volume, litres	334	1255
Temperature range inside unit	-18 to -28	-18 to -28
Refrigerant: R290	Yes	Yes
Compressors	1 pcs	2 pcs
Energy consumption / 24 h kwh at 25 deg. C	3,9	9,2
Input power (watt):	237	580/665
<b>DIMENSIONS</b>		
External dimensions (WxDxH)	1470x812x915	2150x1465x930
Insulation ,mm	80	80
Packing dimension (WxDxH)	1530x920x1000	2240x1550x1050
<b>ACCESSORIES</b>		
Baskets	n/a	n/a
Dividers	Optional	4
Feet	Incl.	Incl.
Bumper bar	Standard	Standard
Extra LED	Optional	Optional
Single or double shelf	Optional	Optional
Price ticket holder	Optional	Optional
<b>OTHER DATA</b>		
Outer cabinet	White	White
Inner cabinet	White	White
Type of cooling	Static	Static
Digital controller	Yes	Yes
HACCP-Hazard analysis System	Yes	Yes
Automatic defrost	Yes	Yes
Power	220 v/ 50 Hz	220 v/ 50 Hz
Power 110 v/ 60 Hz	Optional	Optional
No. of compressors	1	2
Net weight, kg	125	198
Gross weight, kg	85	251
<b>SHIPPING</b>		
20' cont. Capacity	16	6
40' cont. Capacity	30	14
40' HC cont. Capacity	30	14
Standard Trailer capacity	46	16



DSM 220