

# | CT & DUO |

## PERFECT VIEW



CT 5



DUO 127

## FEATURES

- Low service costs
- Perfect view to the products
- Long life
- Graphics (option)

MINIMUM QUANTITY APPLIES

	DUO 80	DUO 127	CT 5
Climate class	3	3	4
Ambient temperature range	+10 to +25	+10 to +25	+16 to +30
Gross volume, litres	123	224	43
Net volume, litres	82	139	43
Temperature range inside unit	-14 to -23	-14 to -23	-14 to -35
Refrigerants available:	R404a / R290	R404a / R290	404a
Energy consumption/ 24 h	9,03 (R290)	14,62 (R290)	2,5 (R404a)
Input power (watt)	447	850	211
<b>DIMENSIONS</b>			
External dim. (WxDxH)	800x750x1178	1270x750x1178	770x570x400
Internal dim. (WxDxH) upper	670x325x380	1140x325x380	379x379x260
Internal dim. (WxDxH) lower	670x530x440	1140x530x440	
Insulation (mm)	60	60	75
<b>ACCESSORIES</b>			
Divider	2 in top section/ 2 in lower section	4 in top section/ 4 in lower section	Optional
Feet	Incl.	Incl.	n/a
Lock	n/a	n/a	Incl.
Thermometer	Analog	Analog	Controller
Digital controller	n/a	n/a	Incl.
Internal light	Incl.	Incl.	n/a
<b>OTHER DATA</b>			
Outer cabinet	White	White	Silver
Inner cabinet	Painted steel	Painted steel	Black
Graphics	Optional	Optional	Optional
Type of cooling	Static	Static	Static
Type of defrost	Manual	Manual	Manual
Power	220 v/ 50 Hz	220 v/ 50 Hz	220 v/ 50 Hz
Power 110 v/ 60 Hz	Optional	Optional	Optional
Net weight, kg	83	123	36
Gross weight, kg	93	135	39
<b>SHIPPING</b>			
20' cont. Capacity	14	11	69
40' cont. Capacity	28	22	192
40' cont. HC Capacity	28	22	n/a
Standard Trailer capacity	64	52	330